WARRANTY

D & R Electronics warrants its new products to be free from defects in material and workmanship, under normal use and service, for a period of one lyear on parts replacement, and one year on labor. This warranty applies only to original purchasers acquiring the product directly from D&R Electronics, or its authorized dealers. Warranty will not be recognized without proof of purchase or bill of sale. This warranty is not transferable. The warranty begins on the date of delivery to the first user/purchaser. This warranty shall not apply to products which must be repaired due to normal wear and tear, negligence, improper installation, abuse, misuse, or which have been altered or modified at a facility other than D & R Electronics, or its authorized depot center. Units proved to be defective within the warranty period, based on an examination by D&R Electronics, will be replaced or repaired at D & R Electronics' option. This warranty does not cover travel expenses or labor charges for removal or installation. Lamps. flash tubes, batteries or other items considered consumables are not covered under warranty. This warranty is in lieu of all other express warranties. D&R Electronics makes no other warranties, expressed or implied, than the express warranties contained herein.

PRODUCT RETURN POLICY

In order to provide you with faster service, product returns for repair or replacement, must have a **Return Goods Authorization Number (RGA number)**. Please contact our company to obtain a RGA number before you return the product to D & R ELECTRONICS. Write the RGA number clearly on the package. Be sure you use sufficient packing materials to avoid damage to the product being returned while in transit. D & R ELECTRONICS assumes no responsibility or liability for expenses incurred for the removal and/or the installation of products requiring service and/or repair. Repairing or replacing product is at the discretion of D & R ELECTRONICS.

D&R Electronics CANADA 8820 George Bolton Parkway Bolton, Ontario, L7E 2Y4 Phone (905) 951-9997 Fax (905) 951-0019 1-800-538-7338 (USA Only) www.DandRElectronics.com

> USA 2321 Kenmore Ave. Buffalo, NY 14207



Product Part Number: 935-0049A Description: Speaker Bracket Model: Dodge Charger / Magnum

INSTALLATION MANUAL



Contents:

Parts List————————————————————————————————————	-'
Installation Instructions—————	-2
Warranty & Product Return Policy	_

Parts List:

Quantity	Part #	Description
1	935-0049A	Speaker Bracket —Centre Mount
4	411-0027	1/4-20x3/4" Bolt, Hex, S.S
8	413-0018	1/4 - 20 flat washer. SS
4	413-0003	1/4 - 20 lock washer, SS
4	412-0002	1/4 -20 Hex nut, SS

REV. JUNE 6, 2015

INSTALLATION INSTRUCTIONS

Features:

The Speaker bracket is designed to fit in front of the vehicle radiator centered behind the vehicle grill.

Vehicle Preparation:

The front end molding must be removed from the vehicle to allow for installation of the speaker bracket and speaker.

Speaker Bracket Preparation:

This product is shipped ready to install. Remove all items from the shipping packaging, confirm contents by comparing with the packing list. Report any shortages or discrepancies to D&R immediately. If the product was damaged in shipment notify the shipping company within 48 hrs. Keep all packing material and documents for presentation to the shipping company.

Speaker Bracket Installation:

The speaker bracket is designed for quick installation on the vehicle.

Note: This product is designed for installation on model year 2005 and newer vehicles.

Basic Installation:

- 1. Remove the front end molding to expose the mounting location (Figure 1)
 - There are; 10 #7 Head Screws on the bottom edge
 - 3 plastic rivets on each side that must be cut off
 - 2 #10 Head screws at each side
 - 8 clips along the top

Pop up a guide pin in the top corners and lift the front end molding off.



Figure 1

2. Hold the bracket and sit it over top of the front bumper beam. With the back plate in place at the back, insert a bolt and washer from the front and tighten on a washer, lock washer and a nut. Do this in each of the 4 corners. Figure 1

Installing speaker

DRCS100 model speakers are installed using the side mounting arms. Refer to installation and wiring instructions included with the speaker for details

DR100R model speakers are installed using the four mounting holes in the rear of the bracket. Refer to the installation instructions included with the speaker for details.



3