GSS


EASY 2 HARNESS INSTALL GPS BASED SPEED SENSOR




- Easy 2 harness connection
- GPS Antenna to be mounted on the roof of the vehicle.
- Closes Odyssey light bar automatically when speed sensor detects speed threshold.
- Can be used even with older model vehicles
- Speed can be set by a 4 pole dip switch (Turn over for Dip Switch settings)
- Possible speed settings from 15 km to 90 Km in increments of 5Km
- Factory default speed set to 30 Km

Canada; 8820 George Bolton Pkwy. Bolton, ON L7E 2Y4 | TF: 800-538-7338 USA: 2299 Kenmore Ave. Building 3, Doors 11-14, Buffalo, NY 14207 ISO 9001:2015 REGISTERED COMPANY


DIP SWITCH SETTINGS—SPEED TRIGGER




SPEED =90 KM/HR




SPEED =85 KM/HR




SPEED =80 KM/HR




SPEED =75 KM/HR




SPEED = 70 KM/HR




SPEED =65 KM/HR




SPEED =60 KM/HR




SPEED =55 KM/HR




SPEED = 50 KM/HR




SPEED =45 KM/HR




SPEED = 40 KM/HR




SPEED =35 KM/HR




SPEED =30 KM/HR



SPEED =25 KM/HR



SPEED =20 KM/HR



SPEED =15 KM/HR

^{*****} For miles divide kilometer value by 1.609 ******